



14" DELUXE 10-326

*Featuring NEW Patented Technology




***NEW**
Spring Loaded Tool-Less
Guide System

No tools needed to quickly adjust your guide bearings



13" Cutting Capacity

Quickly adjust your cutting height up to 13"
Includes Quick Reference Scale




***NEW**
Quick Adjust 6" Tall
Rip Fence System

Easily adjust your fence to either side of the blade



***NEW**
Quick Lock Cast Iron
Trunnion System

Equipped with a large handle and locking arm for rapid adjustment



FEATURES:

- **Motor**
 - Horsepower.....1-3/4 HP TEFC
 - Amps.....14/7
 - Volts.....115/230V, 60Hz
- **Cutting Capacity**
 - Height.....13"
 - Width.....13-5/8"
- **Blade** (Includes 111" x 5/8", 4 TPI, Reg.)
 - Width.....3/16" - 3/4"
 - Length.....111"
 - Blade Speed.....1,445/2,950 FT/MIN
- **Table**
 - Size.....21-1/2" x 15-3/4"
 - Left Tilt.....-7°
 - Right Tilt.....45°
 - Miter Gauge "T" Slot.....(2) 3/4" x 3/8"
 - Height to Floor.....40-1/2"
 - Height to Base.....20-7/8"
 - Fence Size.....18-3/4" x 1-3/4" x 6"



DIMENSIONS:

- **Overall**
 - Height.....76"
 - Width.....33-3/4"
 - Depth.....25"
 - Base Size.....24" x 17-5/8"
 - Dust Port.....1@4"
 - Net Weight.....285 lbs.
 - Shipping Weight.....293 lbs.
 - Shipping Carton.....54-1/2"x17-7/8"x23-7/8"
- **Warranty.....5 Years**

For more information or to find a distributor near you, please visit:

www.rikontools.com

RIKON


AVAILABLE ACCESSORIES

10-326



12-201

LED Gooseneck Worklight
with Magnetic Base and
Magnetic Clip




13-912

Replacement Miter Gauge



13-326

Optional Mobility Kit



C10-326

Replacement Guide Bearings
Pack of 10



Table Inserts

Table Insert - C10-391
Zero Clearance Insert - C10-392
Aluminum Insert - C10-395



C10-995

Replacement Drive Belt



Shown with Optional Mobility Kit
13-326

10-326 Bandsaw Blades

Length	Width	Gauge	TPI	Style	Item No.
111"	3/16"	.025"	10	Reg. Tooth	19-1101
111"	1/4"	.025"	6	Hook Tooth	19-1100
111"	3/8"	.025"	4	Hook Tooth	19-1102
111"	1/2"	.025"	3	Hook Tooth	19-1103
111"	5/8"	.025"	3	Hook Tooth	19-1104
111"	5/8"	.025"	4	Reg. Tooth	19-1105
Bi-Metal					
111"	1/2"	.025"	14	Reg. Tooth	19-1511
111"	1/2"	.025"	18	Reg. Tooth	19-1512
111"	3/4"	.035"	8/12	Var. Tooth	19-1513
111"	3/4"	.035"	10/14	Var. Tooth	19-1514

For more information or to find a distributor near you, please visit:

www.rikontools.com